

Plate bending machines, help for machine selection:

Type(AC/MB7)	Nominal Pressure (kN)	Workbench Length (mm)	Workbench Width (mm)	Poles distance (mm)	Throat depth (mm)	Max Opening Height (mm)	Main motor (kW)	wallboard thickNess (mm)	slipper thickNess (mm)
40T/2200	400	2200	130	1600	200	320	5,5	25	30
40T/2500	400	2500	130	1900	200	320	5,5	25	30
50T/2200	500	2200	160	1600	200	320	5,5	25	35
50T/2500	500	2500	160	1900	200	320	5,5	25	35
63T/2500	630	2500	160	1900	250	345	5,5	30	40
63T/3200	630	3200	160	2600	250	345	5,5	30	40
63T/4000	630	4000	160	3100	250	345	5,5	30	40
80T/2500	800	2500	180	1900	250	350	5,5	35	40
80T/3200	800	3200	180	2600	250	350	5,5	35	40
80T/4000	800	4000	180	3100	250	350	5,5	35	40
80T/5000	800	5000	180	4000	250	380	7,5	35	40
100T/2500	1000	2500	180	1900	320	380	7,5	40	45
100T/3200	1000	3200	180	2600	320	380	7,5	40	50
100T/4000	1000	4000	180	3100	320	380	7,5	40	50
100T/5000	1000	5000	180	4000	320	380	7,5	40	50
100T/6000	1000	6000	200	4800	320	380	7,5	50	60
125T/2500	1250	2500	180	1900	320	380	7,5	50	50
125T/3200	1250	3200	180	2600	320	380	7,5	50	50
125T/4000	1250	4000	180	3100	320	380	7,5	50	50
125T/5000	1250	5000	200	3950	320	380	7,5	50	50
125T/6000	1250	6000	200	4800	320	380	11	50	60
160T/2500	1600	2500	200	1900	320	450	11	50	60
160T/3200	1600	3200	200	2550	320	450	11	50	60
160T/4000	1600	4000	200	3040	320	450	11	60	60
160T/5000	1600	5000	200	3800	400	450	11	60	60
160T/6000	1600	6000	200	4800	400	450	11	60	60
200T/2500	2000	2500	220	1840	350	500	11	60	70
200T/3200	2000	3200	220	2540	350	500	11	60	70
200T/4000	2000	4000	220	3100	350	500	11	60	70
200T/5000	2000	5000	220	3800	350	500	11	60	70
200T/6000	2000	6000	220	4800	350	500	15	60	70
250T/2500	2500	2500	240	1800	350	520	18,5	70	70
250T/3200	2500	3200	240	2500	350	520	18,5	70	70
250T/4000	2500	4000	240	3030	350	520	18,5	70	70
250T/5000	2500	5000	240	4000	350	520	18,5	70	70
250T/6000	2500	6000	260	4830	400	520	18,5	70	70
300T/3200	3000	3200	240	2500	400	520	22	80	80
300T/4000	3000	4000	240	3100	400	520	22	80	80
300T/5000	3000	5000	240	4000	400	520	22	80	80
300T/6000	3000	6000	280	4800	400	520	22	80	80
350T/3200	3500	3200	320	2500	400	540	22	80	80
350T/4000	3500	4000	320	3100	400	540	22	80	80

350T/5000	3500	5000	380	4000	400	540	22	80	80
350T/6000	3500	6000	320	4600	400	540	22	80	80
400T/3200	4000	3200	320	2500	400	540	30	80	90
400T/4000	4000	4000	320	3100	400	540	30	80	90
400T/5000	4000	5000	320	4000	400	540	30	80	90
400T/6000	4000	6000	320	4600	400	540	30	80	90
400T/7000	4000	7000	320	5400	400	540	30	80	90
500T/3200	5000	3200	360	2500	400	620	37	90	90
500T/4000	5000	4000	360	3100	400	620	37	90	100
500T/5000	5000	5000	360	4000	400	620	37	90	100
500T/6000	5000	6000	360	4800	400	620	37	90	100
500T/7000	5000	7000	360	5400	400	620	37	90	100
500T/8000	5000	8000	400	6200	400	620	37	90	100
600T/4000	6000	4000	400	3000	400	620	45	100	110
600T/6000	6000	6000	400	4800	400	620	45	100	110
600T/8000	6000	8000	400	6200	350	620	45	100	110
700T/8000	7000	8000	480	6200	350	630	55	100	110
800T/4000	8000	4000	500	3000	400	680	55	110	120
800T/5000	8000	5000	500	4000	400	680	55	110	120
800T/6000	8000	6000	500	4800	400	680	2×30	110	120
800T/8000	8000	8000	500	6200	400	680	2×30	110	120